



PLUS SHINGELS • APP modified bitumen shingle



Victorian® PLUS - 01 | Black





PLUS SHINGELS • APP modified bitumen shingle

Your Benefits:

- APP modified bitumen shingle
- Superior quality high grade bitumen fibreglass shingle
- Exceeds the most stringent worldwide standards
- Additional UV protection thanks to APP Bitumen
- Higher flexibility with low(er) temperatures



**Armourglass®
PLUS**



**Victorian®
PLUS**



**Diamant®
PLUS**

Width (EN 544)	1000 mm (± 3)	1000 mm (± 3)	1000 mm (± 3)
Height (EN 544)	336 mm (± 3)	336 mm (± 3)	284 mm (± 3)
Weight/m ² covered	± 10,7 kg/m ²	± 10,2 kg/m ²	± 10,4 kg/m ²
Coverage/bundle	2 m ²	2 m ²	2 m ²
Shingels/bundle	14	14	18
Bundles/pallet	66	66	60

Granule adhesion (EN 12039)	max. 1,2 g
Tensile strength (width)* (EN 12311-1)	850 N/50 mm
Tensile strength (height)* (EN 12311-1)	500 N/50 mm
Elongation (width)* (EN 12311-1)	3,00 %
Elongation (height)* (EN 12311-1)	3,00 %
Nails shank tear resistance* (EN 12310-1)	160 N

External fire performance (EN 13501-5)	B _{roof} (t _i)
Reaction to fire (EN 13501-1)	Class E

* Registered average values



IKO Sales International NV

Truibroek 74 • 3945 Ham • Belgium
T +32 (0)11 34 01 20 • F +32 (0)11 34 01 30
E residential.europe@iko.com • www.iko.eu



The information is subject to change without prior notice.
Consult our shingle overview leaflet or website www.iko.eu for colour availability
of the products and application instructions.