#### **IKO SHINGLES THERMO SYSTEM**







Dealer:



#### IKO Sales International NV

Truibroek 74 3945 Ham • Belgium

- **T** +32 (0) 11/34 01 20
- E residential.europe@iko.com

#### www.iko.eu

# NEW SHINGLE 2.0



made in EUROPE  $\overline{\nabla}$ 

n)

lightweight roofing shingles meet today's and tomorrow's expectations in terms of re-



IKO has further enhanced the reliability of the highest quality roofing shingles with the new Shingle 2.0.. IKO roof shingles consist of carefully selected and local European raw materials of a fiberglass inlay, bitumen, and a topcoat of natural stone granules in a variety of colors. We have further refined our recipe for the production of quality shingles.

# IKO believes in continuous evolution and has further enhanced the reliability of the highest quality roofing shingles manufactured in Europe with the new IKO Shingle 2.0.

improve the performance of our products.

Just like the organisms around us, our shingles are undergoing evolution. Our innovations are evolutionary in nature.

For IKO shingle 2.0 we use finer granules. We have also changed the granulometry of the natural stone granulate. "Granulometry means the distribution, composition and texture of particles based on their size ranges." Finer granules allow us to cover the surface of the shingle more homogeneously.

The granulate particles can be more accurately embedded into the bitumen base. This gives us a more compact surface layer. Improved coverage provides the UV protection of the bitumen substrate.

The surface of the 2.0 shingle is more resistant to mechanical damage, thus pushing the test results well above the already high standard of our products in this area.

To even further support this innovation, IKO has also focused on adding an additional extra to the surface finish layer. The granules are finished with a water repellent coating.

Water has a destructive effect on shingles throughout the year. When it freezes in the shingle structure over the winter, it causes a slow release of the stone sprinkle. However, during spring and summer, the shingle structure becomes an environment with optimal conditions for moss growth.

Our aim is to prevent as much as possible the access of water into the structure of the granules. This theory has been proven in the lab. The improved coated granules are less water absorbent and due to its finer structure or granulometry, water has more difficulty of getting through.



# IKO Shingle 2.0:

## The future of roofing is lighter, more durable and European made



# SOLAR PANELS MOUNTING SET

#### - Quick, easy and safe assembly

 Suitable for all shapes of bitumen shingles; new or renovation projects

Set created with premium materials

2 sets available: with Hanger bolt in 200 or 250 mm

# LAMINATED SHINGLES



- Xtreme slope: ≥ 9,5° (!) / ≤ 90°
- Xtreme resistance to high wind & heavy rain
- Xtreme unique: the world's first selfadhesive laminated shingle



53 | Autumn brown



# LAMINATED SHINGLES



- Most efficient laminated shingle in the world: more coverage than any standard shingle
- Cambridge Xpress Lane for improved nailing performance



50 | Harvard slate





	coverage / bundle (max. m²)			
$\bigtriangleup$	bundle coverage (max. m) for hip / ridge			
	bundles / pallet			
right"	weight / m² covered			
	shingles / bundle			





- Upgraded shingle option manufactured with polymer-modified bitumen
- More flexible at low temperatures
- Additional resistance at high temperatures
- Resistant against extreme weather conditions
- Maximum durability due to APP modified bitumen



















- Self-adhesive shingle
- Can be used on steep slope roofs
- driven rain and ice dams
- Exceptional resistance to strong



**36** | Sky blue ultra





\*\* Use Armourglass PLUS shingles





# PLUS SHINGLES

- APP modified bitumen
- Superior quality high grade bitumen fibreglass shingle
- Exceeds the most stringent worldwide standards
- Additional UV protection thanks to APP Bitumen
- Higher flexibility with low(er) temperatures



Black
Amazon green
Dual brown
Tile red
Sky blue
Tile red ultra
Amazon green ultra

27 Dual brown ultra

51 Eastern grey52 Dual black53 Autumn brown54 Aged redwood

49 Earthtone cedar

50 Harvard slate

31 Slate

55 Riviera red







\* Use Superglass shingles

# CLASSIC SHINGLES



- Top quality high grade bitumen fibreglass shingle
- Most popular and time-tested shingle
- Exceptional value for money
- Highly resistant to colour fading



#### VENTS

Armourvent® MULTI	Armourvent® MULTI PLUS	Armourvent <sup>®</sup> RIDGE PLUS		
600 x 22,8 cm	600 x 28,5 cm	122 x 2	27,9 cm	
Monarch® Victorian® PLUS Armourglass® PLUS	Cambridge Xtreme 9,5° Cambridge Xpress Monarch®-Diamant DiamantShield® PLUS ArmourShield® PLUS Diamant® PLUS Superglass®-Hex Superglass®-Biber Superglass®	Cambridge Xtreme 9,5° Cambridge Xpress Monarch®-Diamant DiamantShield® PLUS ArmourShield® PLUS Diamant® PLUS Superglass®-Hex Superglass®-Biber Superglass®		
275 cr min. 16,50 – ma			m²/m * x. 30,97 m²/m **	
≥95°***		$\checkmark$		
		150	45°	
x 10/ T Armourvent®		150	45°	
x 10/ 🗂	x 10/	15°	Arrow Arr Arrow Arrow	
x 10/ Armourvent®	x 10/ The second	۲5°	45° 45° awk <sup>®</sup> Ø = 35,56 cm (14 inc)	
x 10/ The second	x 10/			
x 10/ The second	x 10/ (1) x 10/ (1)	Ø = 30,48 cm (12 inch) Black Brown	Ø = 35,56 cm (14 inc	

			GALL			. Sector Se	Carconstr Set User Statutes	•	IIII	San Angeli	1
Shingle Stick	Plastal Stick	Plastal	G	alvanise nails	ed	G	alvanise nails	ed		OSTITC biled na	
310 ml	310 ml	5 kg		1 kg			5 kg			7200 pcs	
x 12/	x 12/	-	length	pcs.	m²	length	pcs.	m²	length	kg	m²
Premium Elastomeric bitumen based mastic	Elastomeric bitumen based mastic	Elastomeric bitumen based mastic	20 mm 25 mm	± 690 ± 582	± 20 ± 16	20 mm 25 mm 30 mm 35 mm	± 3450 ± 2910 ± 2480 ± 2150	± 98 ± 83 ± 70 ± 61	25 mm 31 mm	12,65 15,10	± 205 ± 205



Armourbase® ECO

Armourbase<sup>®</sup> PRO

SA (self-adhesive)	-	-	overlapping part	full SA
effective coverage area:				
≥ 21° - 85°	90 %	90 %	90 %	90 %
≥ 15° - 20°	50 %	50 %	90 %	90 %
≤ 15°	50 %	50 %	90 %	90 %
l x w (m)	50 x 1	30 x 1	30 x 1	20 x 1
pcs/pallet	20	40	33	45
mm	0,6	0,5	0,5	0,5

#### IKO BASE

An APP modified underlayment under Armourvalley for full adhesion torching on low sloped roofs.

l x w (m)	12 x 1
pcs/pallet	24
mm	2,1







areas adjacent to shingles.

## MASTICS & NAILS





# UNDERLAYS



#### Armourbase<sup>®</sup> **PRO PLUS**

#### Armourbase<sup>®</sup> STICK

#### ARMOURVALLEY

An APP modified roll manufactured in matching shingle colours for use in the valleys of shingle roofs or on low slope roof