



# LAMINATED SHINGELS

Double-layer shingle with "Cambridge Xpress Lane"



Cambridge Xpress - 51 | Eastern grey





# LAMINATED SHINGELS • Double-layer shingle with "Cambridge Xpress Lane"

## Your Benefits:

- Most efficient laminated shingle in the world: larger shingle size (more coverage than any standard shingle) and very quick to install
- Extra large nailing area, known as the "**Cambridge Xpress Lane**", for improved nailing shingle performance (especially on steep roofs) and faster implementation of the shingles
- Double-layer shingle with a dimensional wood shake look in natural tones and colours
- Best choice for the home-owner with its water-shedding and weather-resistant construction
- Excellent solution for renovation projects



Cambridge Xpress

|                               |                          |
|-------------------------------|--------------------------|
| Width* (EN 544)               | 1038 mm (± 3)            |
| Height (EN 544)               | 349 mm (± 3)             |
| Weight/m <sup>2</sup> covered | ± 12,9 kg/m <sup>2</sup> |
| Coverage/bundle               | 2,17 m <sup>2</sup>      |
| Shingles/bundle               | 14                       |
| Bundles/pallet                | 54                       |

|                                           |             |
|-------------------------------------------|-------------|
| Granule adhesion (EN 12039)               | max. 1,2 g  |
| Tensile strength (width)* (EN 12311-1)    | 850 N/50 mm |
| Tensile strength (height)* (EN 12311-1)   | 550 N/50 mm |
| Elongation (width)* (EN 12311-1)          | 3,50 %      |
| Elongation (height)* (EN 12311-1)         | 3,50 %      |
| Nails shank tear resistance* (EN 12310-1) | 140 N       |

|                                        |                      |
|----------------------------------------|----------------------|
| External fire performance (EN 13501-5) | Broof(t1), Broof(t3) |
| Reaction to fire (EN 13501-1)          | Class E              |

\* Registered average values



The information is subject to change without prior notice.  
Consult our shingle overview leaflet or website [www.iko.eu](http://www.iko.eu) for colour availability of the products and application instructions.



IKO Sales International NV  
Truibroek 74 • 3945 Tessenderlo-Ham • Belgium  
T +32 (0)11 34 01 20 • F +32 (0)11 34 01 30  
E [residential.europe@iko.com](mailto:residential.europe@iko.com) • [www.iko.eu](http://www.iko.eu)

